

	Übersicht EcoFlow Power Station RIVER			Übersicht EcoFlow Power Station DELTA				Benzingenerator	
	EcoFlow Power Station RIVER 2	EcoFlow Power Station RIVER 2 MAX	EcoFlow Power Station RIVER 2 PRO	EcoFlow Power Station DELTA 2	EcoFlow Power Station DELTA	EcoFlow Power Station DELTA MAXS	EcoFlow Power Station DELTA MAX	EcoFlow Power Station DELTA PRO	EcoFlow Smart Generator
									
	Art. EFRiver2	Art. EFRiver2/MAX	Art. EFRiver2/PRO	Art. EFDelta2	Art. EFDelta	Art. EFDelta/MAXS	Art. EFDelta/MAX	Art. EFDelta/PRO	Art. EFGenerator
Kapazität	256 Wh	512 Wh	768 Wh	1'024 Wh	1'260 Wh	1'612 Wh	2'016 Wh	3'600 Wh	
AC-Ausgang (Spitze)	300 W (600)	500 W (1'000)	800 W (1'600)	1'800 W (2'700)	1'800 W (3'300)	2'000 W (4'600)	2'400 W (4'600)	3'600 W (7'200)	1'800 W (1'900)
X-Boost	600 W	1'000 W	1'600 W	2'400 W		2'800 W	3'400 W	4'500 W	
Anzahl AC-Ausgänge	1	2	3	4	4	4	4	4	1 x 230 V 1 x Anschluss für Zusatzbatterie
DC-Ausgang	1 x 12.6 V, 8 A	1 x 12.6 V, 10 A	1 x 12.6 V, 10 A	1 x 12.6 V, 10 A	1 x 13.6 V, 8 A	1 x 12.6 V, 10 A	1 x 12.6 V, 10 A	1 x 12.6 V, 10 A 1 x 12.6 V, 30 A	
USB-C Anschlüsse	1 x max. 60 W	1 x max. 100 W	1 x max. 100 W	2 x max. 100 W	2 x max. 60 W	2 x max. 100 W	2 x max. 100 W	2 x max. 100 W	
Aufladen 230 V, X-Stream	max. 360 W	max. 660 W	max. 940 W	max. 1'200 W	max. 1'200 W	max. 2'000 W	max. 2'000 W	max. 2'500 W	
Ladedauer an Wandsteckdose	1.0 h	1.0 h	1.2 h	1.2 h	1.6 h	1.6 h	1.6 h	1.9 h	
Ladedauer des Solarmoduls	2.5 - 5.0 h (1 x 110 W)	2.5 - 5.0 h (1 x 220 W)	3.5 - 7.0 h (1 x 220 W)	3.0 - 4.0 h (1 x 500 W)	4.0 - 8.0 h (1 x 400 W)	3.2 - 6.3 h (2 x 400W)	3.2 - 6.3 h (2 x 400W)	4.0 - 8.0 h (3 x 400W)	
Gewicht	3.5 kg	6.0 kg	7.8 kg	12.0 kg	14.0 kg	21.5 kg	22.0 kg	45.0 kg	28.5 kg
Abmessungen	245 x 214 x 142 mm	270 x 260 x 196 mm	270 x 260 x 226 mm	400 x 211 x 281 mm	400 x 210 x 270 mm	497 x 242 x 305 mm	497 x 242 x 305 mm	635 x 285 x 541 mm	597 x 296 x 475 mm
Car Charger	12/24 V DC, 8 A	12/24 V, 13 A	12/24 V, 13 A	12/24 V DC, 8 A	12/24 V DC, 8 A	12/24 V DC, 8 A	12/24 V DC, 8 A	12/24 V DC, 8 A	
Solar Charger	110 W, 11-30 V, 8 A	220 W, 11-30 V, 13 A	220 W, 11-30 V DC, 13 A	500 W, 11-60 V DC, 15 A	400 W, 10-65 V DC, 10 A	800 W, 11-100 V DC, 13 A	800 W, 11-100 V DC, 13 A	1'600 W, 11-150 V, 15 A	
Connectivity	WiFi, Bluetooth	WiFi, Bluetooth	WiFi, Bluetooth	WiFi, Bluetooth	keine App-Anbindung	WiFi	WiFi	Wifi und BT Aufladen an EV-Ladestationen	elektrischer Start mittels App-Steuerung
Batterietyp	LiFePO <sub>4</sub>	LiFePO <sub>4</sub>	LiFePO <sub>4</sub>	LiFePO <sub>4</sub>	Li-Ion	NCM	NCM	LiFePO <sub>4</sub>	
Ladezyklen	3'000, min. 80%	3'000, min. 80%	3'000, min. 80%	3'000, min. 80%	800, min. 80%	800, min. 80%	800, min. 80%	3'500, min. 80%	

## ZUBEHÖR ZU DEN ECOFLOW POWER STATIONS



Weiteres Zubehör zu den EcoFlow Power Station finden Sie auf unserer Website <https://eu.ecoflow.com/>

